

PN=JP 59204920

1/3,AB,LS/1 (Item 1 from file: 351)
DIALOG(R)File 351:Derwent WPI
(c) 2004 Thomson Derwent. All rts. reserv.

004177153

WPI Acc No: 1985-004033/ 198501

XRAM Acc No: C85-001809

Heat and chemical resistant conjugate fibre - has polyester core and
sheath comprising polymer based on polyphenylene sulphide

Patent Assignee: KURARAY CO LTD (KURS)

Number of Countries: 001 Number of Patents: 002

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 59204920	A	19841120	JP 8377961	A	19830502	198501 B
JP 92001085	B	19920109	JP 8377961	A	19830502	199206

Priority Applications (No Type Date): JP 8377961 A 19830502

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 59204920	A		3		

Abstract (Basic): JP 59204920 A

The conjugate fibre has (A) a core component consisting of polyester and (B) a sheath component consisting of a polymer in which polyphenylene sulphide accounts for at least 80 wt.%, with the ratio of (B) to (A+B) ranging from 0.05-0.4 (0.1-0.3) in the cross section of the fibre.

The polyester for (A) is made from aromatic or aliphatic dicarboxylic acid or its ester and diol cpds. It may contain a comonomer such as polyalkylene glycol and sulpho-isophthalic acid and less than 10 wt.% of known additives. Pref. is a polyester in which polyethylene terephthalate accounts for at least 95 wt.% and which has a limiting viscosity number of 0.05-1.0 dl/g. Pref. (B) is prepd. by blending less than 20% of polyester.

ADVANTAGE - The conjugate fibre has excellent resistance to heat and chemicals and retains characteristics inherent to polyester.

0/0